

# ARP Traffic Study

Jim Rees, Manish Karir  
Research and Development  
Merit Network Inc.


# Outline

- Goals
- Experiment Setup and Architecture
- Experiments
  - Scanning
  - Number of hosts
  - Traffic load/patterns
  - Host failures
  - VM Migrations
- Conclusions

# ARP/ND Traffic Study

- Attempt to understand ARP behavior under various conditions
- Recreate various environments and observe ARP/ND traffic
- Build a model of ARP/ND based on experiments and collected data
- Build scalable ARP/ND emulator for large scale experiments which can mimic various environments for evaluating software/protocol impact, and perhaps proposed solutions

# Network Topology



# Experiment Setup

- VMWare Cloud Director
  - Resource Pool – 100GHz, 200GB RAM, 3TB Disk
  - 60 Vapps with 10 VMs each
  - Each VM 4G disk 256MB RAM – Centos 5.5
  - Single flat network topology /22 network block
  - Roughly 500 VMs used in tests
- Herding the bot
  - Write command/control agent/controller software
  - Allows us to issue commands to all bots to start/stop services
  - Write traffic generator software to generate internal and external traffic load via a traffic matrix



# Traffic Generator

- Runs on upto 500 hosts
- Each host listens for commands from controller and also runs web server
- Bot controller sends UDP broadcast message hosts to start/stop (no ARP traffic)
- Each host has list of other hosts to contact
- For each host on list:
  - wget <https://host> (v4/v6)
  - sleep(n seconds - configurable)
- Host list updated on each host prior to experiment

# Initial Experiments

- Effect of external scans
- Effect of number of hosts and relative traffic load
- Effect of machine failures
- Effect of traffic load with same number of hosts
- Effect of VM migrations
- IPv6 neighbor discovery behavior (for all above)


# I: Effect of External Scans




- nmap scans from outside the network
- Measure ARP/ND traffic spikes
- Monitor CPU load on access switch
- Possible to cause transient spikes in ARP/ND traffic
- Affect on CPU load is greater for ARP than ND



# 1. Effect of External Scans (single)




## II: Effect of Number of Hosts




- Starting up up to 500 hosts  
100,200,300,400,500
- Stop all hosts in between batch starts
- Measure startup ARP/ND traffic and CPU Load
- Increase overall traffic load roughly 5x from 100 – 500 hosts
- Initial spike in CPU load similar for both v4/v6
- Roughly linear increase in ARP/ND traffic
- Higher ARP traffic rate as compared with ND

# IIb: Effect of Traffic




- Starting up 500 hosts
- Hosts attempt to contact varying number of active/inactive hosts (500/0, 400/100, 300/200, 200/300, 100/400)
- Highest possible rate zero sleep
- Stop all hosts in between changes to traffic pattern
- Measure startup ARP/ND traffic and CPU Load
- Initial spike in CPU load slightly higher for both ARP
- CPU load spike roughly same across traffic patterns
- Roughly linear increase in ARP/ND traffic
- Higher ARP traffic rate as compared with ND

# IIC: Effect of Number of Hosts/Traffic




- Starting up all 500 hosts
- Contact list includes all 500 hosts plus a varying number of inactive hosts(0, 100, 200, 300, 400)
- Sleep 2 seconds between connects
- Stop all hosts in between experiments
- Measure startup ARP/ND traffic and CPU Load
- Initial spike in CPU load similar for both v4/v6
- Roughly linear increase in ARP/ND traffic
- Slight increase in CPU load for v6
- Higher ARP traffic rate as compared with ND

# III: Effect of Machine Failures





- Start Traffic generator on 400 hosts, 80 targets
- Shutdown targets in groups of 10
- Measure ARP traffic and CPU Load
- ARP traffic increases as number of failed machines increases

# IV: Effect of VM Migrations




- Start Traffic generator on 500 hosts
- Roughly 36 VMs on 1 blade
- Place blade into maintenance mode forcing all VMs on that blade to migrate to other blades
- Measure ARP Traffic

# V: Effect of Traffic Load



- Start Traffic generator on 500 hosts
- Vary the amount of load by reducing time between communication events (50, 20, 10, 5, 2, 1 seconds)
- Measure ARP/ND Traffic and CPU load on switch
- ARP/ND increases roughly linearly across experiments

# VI: Highest possible Load



- Start traffic generator on 500 hosts
- All hosts communicate with all other hosts as fast as possible (sleep interval = 0)
- 30 second test
- Maximum 4K pps of ARP pkts and a CPU load of 65



# Conclusion and Next Steps

- There appears to be roughly linear relationship between ARP traffic and number of hosts and traffic
- There can be scenarios where machine failures in a data center can lead to higher ARP traffic rates
- Overall ND appears to be lower impact than ARP in terms of traffic volume, number of hosts, and CPU load on access switch as compared with ARP
- Detailed analysis of collected ARP/ND traffic
- Build model of ARP/ND traffic behavior based on experimental data
- Build ARP/ND traffic emulator software to scale up the experiments
- Move away from limitations of managing real VM hosts
- Repeat measurements for live production environment and compare with our experimental setup